

SUCTION LIFTER & TILE VIBRATOR



3300 LEVER-ACTIVATED SUCTION CUPS

VACUUM LIFTER, 3 SUCTION CUPS

- Lever action, aluminium body lifter for carrying heavy glass.
- Suitable for all materials with smooth, airtight surfaces such as glass, plastic, metal, coated wood, marble etc.
- Spare suction discs are supplied complete with suction pad, lever, bolt, spring and pressure plate.







Item No. 33000003E

VACUUM LIFTERS, 2 SUCTION CUPS

- For all kinds of loads.
- Quick action flip lever lifters for carrying glass, installing computer floors, etc.
- Equipped with an additional sealing lip, also suitable for slightly curved or textured surfaces.
- Spare suction discs are supplied complete with suction pad, lever, bolt, spring and pressure plate.







Item No. 33000004E



SINGLE LEVER LIGHTWEIGHT VACUUM LIFTER

- A lightweight vacuum lifter for horizontal lifting applications.
- Ideal for lifting computer floors.
- For use on flat surfaces only.
- For all kinds of loads.
- The split handle allows one-handed operation and thus quick, efficient work.



Item No. 33000006E

ITEM NO.	DESCRIPTION	MAX SUCTION LIFTING CAPACITY	COLOUR	PAD SIZE (MM)
3300001E	3-cup Suction Cup,heavy duty	210kg	Black	3x120mm
3300002E	2-cup Suction Cup,heavy duty	135kg	Black	2x120mm
3300003E	3-cup Suction Cup	155kg	Yellow, Bright Surface	3x120mm
3300004E	2-cup Suction Cup	100kg	Yellow, Bright Surface	2x120mm
3300005E	2-cup Suction Cup, swivel head	85kg	Yellow, Bright Surface	2x120mm
3300006E	1-cup Suction Cup	50kg	Yellow, Bright Surface	116mm



3301 ADJUSTABLE ANGLE SUCTION CUPS

ANGLE SUCTION HOLDER, INFINITELY ADJUSTABLE FROM 45° TO 270°

- Very robust model with twin suction units and 2 suction pads (ø118mm) with special sealing lip adjustable +/- 20mm
- · Can be fine adjusted to each other
- Sturdy plastic arms are 194 mm long and are connected to each other by a joint



Item No. 33010001E



SUCTION HOLDER WITH MIDPOINT JOINT

- Universal suction holder for positioning mitres when building showcases, aquari-
- Suitable for all materials like glass, plastic, metal, coated wood and marble.

Suction pad ø118mm







ITEM NO.	DESCRIPTION	PAD DIA.	ADJUSTABLE ANGLE SCOPE	MAX SUCTION LIFTING CAPA	COLOUB
33010001E	2-cup Adjustable Angle Suction Plate	Ø118mm	45° - 270°	35kg	Yellow, Bright Surface
33010002E	2-cup Adjustable Angle Suction Plate	Ø118mm	90° - 270°	35kg	Yellow, Bright Surface



3300 | REPLACEMENT PARTS FOR SUCTION CUPS







WASHER



SPRING



RUBBER PAD

ITEM NO.	DESCRIPTION	PAD DIA.	FITS CUP	
33000020E	Rubber Pad	Ø128mm	3300 series	
33000021E	Rubber Pad	Ø118mm	3301 series	

3302 ANGLE SUCTION HOLDER 90

APPLICATION: For the fixation of two glass plates at right angle.



Item No. 33020002E



Item No.: 33020003E



Sealing lip adjustable +/-20mm Can be fine adjusted to each other

Item No. 33020001E

ITEM NO.	DESCRIPTION	PAD DIA.	ADJUSTABLE ANGLE SCOPE	MAX SUCTION LIFTING CAPACIT	-y COLOUR
33020001E	2-cup Right Angle Suction Cup	Ø118mm	N/A	35kg	Yellow, Bright Surface
33020002E	2-cup Right Angle Suction Cup	Ø56mm	75 x 75 x 75mm	N/A	N/A
33020003E	2-cup Right Angle Suction Cup	Ø75mm	95 x 95 x 95mm	N/A	N/A





3310 SMALL SUCTION CUPS







Item No. 33100002E

Finger lifter ideal for sucking and removing light and thin glass plate. Always handy and ready for use, yet leaves hand free for other work.

ITEM NO.	DESCRIPTION	PAD DIA.	MAX SUCTION LIFTING CAPACITY
33100001E	1- cup Small Suction Cup	Ø 56mm	8kg
33100002E	1- cup Small Suction Cup	Ø 75mm	15kg

3303 PUMP-ACTION VACUUM SUCTION CUPS

- •Pump-activated vacuum mechanisms and quick release triggers
- •A solid one-body frame for durability and safety. It needs only minimum amount of time to activate with the lexan pump and release with one touch button and the rubber rib.
- •Suction lifter made of sturdy aluminium with special suction pad for curved or flat surfaces.
- •A subordinate handle for an extra grip and easy carrying.
- •Suitable for materials with airtight surfaces such as glass, plastic, metal, coated wood, marble etc.



Item No. 33030004E



Item No. 33030008E

Vacuum Suction Lifter with Vertical Handle Especially suitable for windscreen installation, however the unit can be applied to many lifting tasks.

ITEM NO.	DESCRIPTION	PAD DIA.	WORK TEMPERATURE	MAX SUCTION LIFTING CAPACITY	COLOUR	SURFACE ATTACHMENT
33030004E	PUMP SUCTION CUP	Ø254mm/10"	indoor temperature	50-150kgs	Red & Black	Flat & Curved
33030008E	PUMP SUCTION CUP	Ø150mm/6"	indoor temperature	25kgs	Red & Black	Flat & Curved



3303 / 3312 PUMP-ACTION VACUUM SUCTION CUPS

PUMP-ACTION VACCUM SUCTION CUP



Specification:

Pad size:	200mm (8")
Pad material:	single layer rubber
Max load capacity:	150kgs (331lbs)
Load surface:	flat

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Fast attach and release
- ·Red-line indicator warns user of any significant vacuum loss
- ·Supplied with protective carrying case

VACUUM SUCTION CUP WITH PRESSURE GAUGE

33120301O



Specification:

Pad size:	200mm (8")
Pad material:	double layer rubber
Max load capacity:	200kgs (441lbs)
Load surface:	flat
Vacuum gauge:	Yes

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Fast attach and release
- ·Red-line indicator warns user of any significant vacuum loss
- ·Intelligent pressure display: Built-in barometer, data monitoring, real-time control of air pressure during operation.
- ·Supplied with protective carrying case.

VACUUM SUCTION CUP WITH SMALL PRESSURE GAUGE

33120302O



Specification:

200mm (8")
double layer rubber
200kgs (441lbs)
flat
Yes

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

- ·Fast attach and release
- ·Red-line indicator warns user of any significant
- ·Intelligent pressure display: Built-in barometer, data monitoring, real-time control of air pressure during operation.
- Supplied with protective carrying case.



3313

3313 CORDLESS VACUUM SUCTION CUPS

BATTERY POWERED SUCTION CUP

33130301O



Specification:

Pad size:	200mm (8")
Pad material:	single layer rubber
Maxload capacity:	150kgs (331lbs)
Load surface:	flat
Batteries:	3.7V 900mAh Li-ion
Rated power:	3.5W
Number of uses:	>500/day
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Powered by rechargeable battery.
- ·Automatic on/off pump
- ·Portable suction cups for out door application.
- ·Easy for suck and release
- Supplied with protective carrying case

BATTERY POWERED SUCTION CUP

33130302O



Specification:

Pad size:	200mm (8")
Pad material:	single layer rubber
Max load capacity:	200kgs (441lbs)
Load surface:	flat
Batteries:	3.7V 1200mAh Li-ion
Rated power:	3.5W
Number of uses:	>600/day
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Powered by rechargeable battery.
- ·Automatic on/off pump
- ·Portable suction cups for out door application.
- ·Easy for suck and release
- Supplied with protective carrying case

BATTERY POWERED SUCTION CUP

33130303O



Specification:

Pad size:	200mm (8")
Pad material:	double layer rubber
Max load capacity:	200kgs (441 lbs)
Load surface:	flat
Batteries:	3.7V 1200mAh Li-ion
Rated power:	3.5W
working hours:	>8 hours
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

- ·Powered by rechargeable battery.
- ·Automatic on/off pump
- ·Portable suction cups for out door application.
- ·Easy for suck and release
- ·Supplied with protective carrying case



3313 DIGITAL VACUUM SUCTION CUPS

DIGITAL BATTERY POWERED SUCTION CUP

33130304O



Specification:

200mm (8")
double layer rubber
200kgs (441 lbs)
flat
3.7V 2400mAh Li-ion
3.5W
>8 hours
USB-C Charging Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass,plastic, metal, coated wood,tile or marble etc.

Features:

- ·Powered by rechargeable battery with digital display.
- Showing both barometric pressure and battery power level.
- ·Automatic on/off pump
- Portable suction cups for out door application.
- ·Easy for suck and release
- ·Supplied with durable carrying case

DIGITAL BATTERY POWERED SUCTION CUP

33130305O



Specification:

Pad size:	200mm (8")
Pad material:	double layer silicone gel
Max load capacity:	200kgs (441lbs)
Load surface:	flat
Batteries:	3.7V 2400mAh Li-ion
Rated power:	3.5W
working hours:	>8 hours
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Powered by rechargeable battery with digital display.
- Showing both barometric pressure and battery power level.
- ·Automatic on/off pump
- ·Portable suction cups for out door application.
- ·Easy for suck and release
- ·Supplied with protective carrying case

DIGITAL BATTERY POWERED SUCTION CUP WITH SMALL PRESSURE GAUGE

33130306O



Specification:

•	
Pad size:	220mm (9")
Pad material:	double layer rubber
Max load capacity:	250kgs (551lbs)
Load surface:	flat
Vacuum gauge:	Yes
Batteries:	3.7V 2400mAh Li-ion
Rated power:	3.5W
working hours:	>8 hours
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

- ·Fast attach and release
- ·Intelligent pressure display:
- Built-in barometer, data monitoring, real-time control of air pressure during operation.
- ·Digital screen on battery housing shows current power level.
- ·Supplied with protective carrying case



3313 / 3314 SUCTION CUPS AND REPLACEMENT ELECTRIC PUMPS

DIGITAL BATTERY POWERED SUCTION CUP WITH FLEXIBLE EDGE





REPLACEMENT ELECTRIC PUMP WITH AUTO-AIR REPLENISHMENT FOR VACUUM SUCTION CUF

33140301



REPLACEMENT ELECTRIC PUMP WITH TIME AIR-REPLENISHMENT FOR VACUUM SUCTION CUP



DIGITAL BATTERY PACK REPLACEMENT 33140303



Specification:

Pad size:	210mm (8-1/4")
Pad material:	Soft rubber
Max load capacity:	200kgs (441lbs)
Load surface:	Curved
Batteries:	3.7V 2400mAh Li-ion
Rated power:	3.5W
working hours:	>8 hours
Charging line:	USB-C Cable

Application:

Suitable for lifting large panel materials with smooth/Slight Texture surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features

·Fast attach and release.

·Flexible vacuum pad edge for fast attachment to flat or curved surfaces.

Digital display showing both barometric pressure and power level.

·Not for use with thin, fragile materials.

·Not for use with materials thinner than 3mm(1/8").

·Ideal Uses: Curved or irregular nonporous surfaces.

Supplied with protective carrying case.

Specification:

Voltage:	3.7V
Battery capacity:	900mAh
Charging time:	4 hours
Continue work time:	3-5 days

Application:

Replacement for both manual and electric vacuum suction cups.

Features:

·Battery powered Air Vacuum Pump.

·Automatically turn on/off pump.

One-button start, easy to operate, no need to manually press multiple times to replenish air.

Digital display shows the current vacuum air

pressure value and battery power level.

·Automatic air replenishment for air leakage.

Specification:

Voltage:	3.7V
Battery capacity:	1200mAh
Charging time:	5 hours
Continue work time:	5-7 days

Application:

Replacement for both manual and electric vacuum suction cups.

Features:

·Battery powered air vacuum pump.

Automatically turn on/off pump.

One-button start,easy to operate, no need to manually press multiple times to replenish air.

Digital display shows the current vacuum air pressure value and battery power level.

·Automatic air replenishment for air leakage.

·High capacity li-ion battery ensures longer work time.

Specification:

Output voltage:	3.7V
Battery capacity:	2400 mAh
Charging voltage:	5V

Application:

Replacement only for digital vacuum suction cup lifter.

Features:

Extra large capacity li-ion battery ensures longer work time..

·Packed battery ensure safe and explosion-proof.

Digital display shows the current battery level.



3313 SMART SUCTION CUP

SMART SUCTION CUP

33130308O



Specification:

Pad size:	200mm (8")
Pad material:	double layer rubber
Maxload capacity:	150kgs (331lbs)
Load surface:	flat and slightly rough
Batteries:	3.7V 1200mAh Li-ion
Rated power:	3.5W
Number of uses:	>500/day
Charging line:	USB-C Cable
Charging Time:	3 hours
Battery Life:	3-5 days

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood, tile or marble,etc.

Features:

- ·Automatic pressure maintenance and automatic air supply.
- ·External exhaust+automatic cleaning and dust removal.
- ·Suitable forsmooth and slightly rough tiles.
- ·Built in replaceable 1200mAh lithium battery
- ·Integrated digital displayscreen.
- Long press to turn on/off, short press to start, double click to release pressure, triple tap for automatic cleaning.

SMART SUCTION CUP

33130309O



Specification:

Pad size:	200mm (8")
Pad material:	double layer rubber
Maxload capacity:	170kgs (331lbs)
Load surface:	flat and slightly rough
Batteries:	3.7V 1200mAh Li-ion
Rated power:	3.5W
Number of uses:	>500/day
Charging line:	USB-C Cable
Charging Time:	3 hours
Battery Life:	3-5 days

Application:

Suitable for lifting large panel materials with smooth airtight surfaces such as glass, plastic, metal, coated wood,tile or marble,etc.

- ·Automatic pressure maintenance and automatic air supply.
- ·External exhaust+automatic cleaning and dust removal.
- Double filtering.
- ·Suitable forsmooth and slightly rough tiles.
- ·Built in replaceable 1200mAh lithium battery
- ·Integrated digital displayscreen.
- ·Long press to turn on/off, short press to start, double click to release pressure, triple tap for automatic cleaning.



3313 SMART SUCTION CUP

SMART SUCTION CUP



Specification:

Pad size:	160*247mm
Pad material:	double layer rubber
Maxload capacity:	260kgs (331lbs)
Load surface:	flat and slightly rough
Batteries:	7.4V 1200mAh Li-ion
Rated power:	7W
Number of uses:	>500/day
Charging line:	USB-C Cable
Charging Time:	3 hours
Battery Life:	5-7 days

Application:

Suitable for lifting materials with smooth and slightly rough surfaces such as glass, plastic, metal, coated wood, tile or marble, etc.

Features:

- ·Automatic pressure maintenance and automatic air supply.
- ·External exhaust+automatic cleaning and dust removal.
- ·Integrated digital display screen.
- ·Double filtering.
- ·Dual motor.
- ·Long press to turn on/off, short press to start, double click to release pressure,triple tap for automatic cleaning.

SMART SUCTION CUP



Specification:

Pad size:	210mm (8-1/4")
Pad material:	double layer rubber
Maxload capacity:	220kgs (331lbs)
Load surface:	flat and slightly rough
Batteries:	7.4V 1200mAh Li-ion
Rated power:	3.5W
Number of uses:	>500/day
Charging line:	USB-C Cable
Charging Time:	3 hours
Battery Life:	5-7 days

Application:

Suitable for lifting materials with smooth and slightly rough surfaces such as glass, plastic, metal, coated wood, tile or marble,etc.

- Automatic pressure maintenance and automatic air supply.
- ·External exhaust+automatic cleaning and dust removal.
- ·External replaceable2000mAh lithium battery
- Integrated digital display screen.
- ·Double filtering.
- ·Long press to turn on/off, short press to start, double click to release pressure,triple tap for automatic cleaning.



12V TILE VIBRATION

65090305O



Specification:

Battery:	DC12V
Switch:	9 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	160mm(6.3")
Suction weight:	50kg(110lbs)
Tile size:	30-80cm
Packing size:	51.5x39x55cm
QTY/CTN:	6pcs
Weight:	20kgs

Application:

Suitable for home improvement in laying 30-80cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

Features:

- · 9 vibrating frequency setting fit the needs of any project.
- · One touch button to turn on power and switch the speeds.
- One press button to start vibration.
- · One click handle for adsorption and releasing pressure.
- · A bubble level vial on head helps lay tiles more flatter.

12V TILE VIBRATION

65090306O



Specification:

Battery:	DC12V
Switch:	6 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	160mm(6.3")
Suction weight:	50kg(110lbs)
Tile size:	30-80cm
Packing size:	51.5x39x55cm
QTY/CTN:	6pcs
Weight:	20kgs

·Suitable for home improvement in laying 30-80cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile thus facilitating ideal adhesion between the adhesive and the tile

- ·9 vibrating frequency setting fit the needs of any
- One press button to start vibration.
- One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge level.



20V TILE VIBRATOR WITH PLASTIC HEAD

65090307O



Specification:

Battery:	DC20V
Switch:	12 Speeds
Vibrating frequency:	3500-8500r/min
Suction cup diameter:	123mm(4.8")
Suction weight:	45kg(99lbs)
Tile size:	60-120cm
Packing size:	53.5x42.5x53cm
QTY/CTN:	6pcs
Weight:	21.5kgs

Application:

- Suitable for home improvement in laying 60-120cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile.thus facilitating
- ideal adhesion between the adhesive and the tile.

- ·12 vibrating frequency setting fit the needs of any project.
- One touch button to turn on power and switch the speeds.
- One press button to start vibration.
- One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge
- ·A bubble level vial on on auxiliary handle helps lay tiles more flatter.

20V TILE VIBRATION

65090308O



Specification:

Battery:	DC20V
Switch:	12 Speeds
Vibrating frequency:	3500-8800r/min
Suction cup diameter:	123mm(4.8")
Suction weight:	60kg(132lbs)
Tile size:	60-120cm
Packing size:	53.5x42.5x53cm
QTY/CTN:	6pcs
Weight:	20kgs

Application:

Suitable for home improvement in laying 60-120cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

- ·12 vibrating frequency setting fit the needs of any project.
- One touch button to turn on the power and switch the
- One touch button to start vibration.
- ·One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge level.



20V TILE VIBRATION

65090309O



Specification:

Battery:	DC20V
Switch:	12 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	130mm(5-1/8")
Suction weight:	60kg(132lbs)
Tile size:	60-120cm
Packing size:	53x42.5x53cm
QTY/CTN:	6pcs
Weight:	21.5kgs

Application:

- ·Suitable for home improvement in laying 60-120cm tiles.
- Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

Features:

- ·12 vibrating frequency setting fit the needs of any project.
- ·One touch button to turn on the power and switch the speed.
- One touch button to start vibration.
- One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge level.

20V TILE VIBRATION

65090310O



Specification:

DC20V
9 Speeds
3000-8000r/min
160mm(6.3")
70kg(154lbs)
60-120cm
51.5x39x55cm
6pcs
20kgs

Application:

- Suitable for home improvement in laying 60-120cm tiles. Designed to prevent the generation of encapsulated air
- bubbles between the adhesive and the back of the ceramic tile, thus facilitating

ideal adhesion between the adhesive and the tile.

- ·9 vibrating frequency setting fit the needs of any project.
- One touch button to turn on the power and switch the speed.
- One touch button to start vibration.
- One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge
- ·A bubble level vial on on head helps lay tiles more flatter.



20V TILE VIBRATION

65090311O



Specification:

Battery:	DC20V
Switch:	12 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	160mm(6.3")
Suction weight:	100kg(220lbs)
Tile size:	80-150cm
Packing size:	51.5x39x55cm
QTY/CTN:	6pcs
Weight:	21kgs

Application:

Suitable for home improvement in laying 80-150cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

- ·12 vibrating frequency setting fit the needs of any project.
 ·One touch button to turn on the power and switch the speed.
- ·One touch button to start vibration.
- ·One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge
- ·A bubble level vial on auxiliary handle helps lay tiles more flatter.

20V TILE VIBRATION

65090312O



Specification:

Battery:	DC20V
Switch:	9 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	190mm(7-1/2")
Suction weight:	100kg(220lbs)
Tile size:	80-230cm
Packing size:	55x45x55cm
QTY/CTN:	6pcs
Weight:	21.5kgs

Application:

·Suitable for home improvement in laying 80-230cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

- ·9 vibrating frequency setting fit the needs of any project. ·LED display on battery tells the user the remaining charge
- ·Power switch on head with LED display to select the 1-9 vibrating frequencies.
- ·A bubble level vial on auxiliary handle helps lay tiles more flatter.
- ·LED light for working in dark places.
- One press button to start vibration.
- One click handle for adsorption and releasing pressure.



20V TILE VIBRATION

65090313O



Specification:

Battery:	DC20V
Switch:	12 Speeds
Vibrating frequency:	3000-8000r/min
Suction cup diameter:	190mm(7-1/2")
Suction weight:	100kg(220lbs)
Tile size:	80-230cm
Packing size:	55x45x55cm
QTY/CTN:	6pcs
Weight:	21.5kgs

Application: Suitable for home improvement in laying 80-230cm tiles. Designed to prevent the generation of encapsulated air bubbles between the adhesive and the back of the ceramic tile, thus facilitating ideal adhesion between the adhesive and the tile.

- ·12 vibrating frequency setting fit the needs of any project.
- One touch button to turn on the power and switch the
- One touch button to start vibration.
- ·One click handle for adsorption and releasing pressure.
- ·LED display on battery tells the user the remaining charge





Enjoy Work! Enjoy Life!

www.starcraftools.com



Add:No.880 Xingwen Road; Jiading,Shanghai, China Tel:0086-21-33517000,33517100 Email:sales@starcraftgroup.com Copyright©2025